Xenia Wall

inter•lux

IP66

Contents

2	product configurator
3	diagrams / drivers
4	photometry





14.4" (6.4W CV / 7.2W IND)
24.8" (11W CV / 12.3W IND)
36.6" (16.5W CV / 18.5W IND)
48.4" (22W CV / 24.6W IND)
60.2" (27.5W CV / 30.8W IND)

General: Xenia is a family of slim profile, low glare linear LED recessed and wall fixtures suitable to illuminate outdoor architectural elements such as facades, columns, landscape, and pathway lighting. The recessed version can be installed as a drive-over in-grade or can be mounted into walls and ceilings. The wall version offers several mounting brackets and anti-glare visors to direct light only where needed. Multiple optics, internal Micro-louvers and a PRO version for higher output complete the range.

Fixture Body: Corrosion resistant 6060 Aluminum, Anodized (20 µm).
Trim: Frameless, ideal for continuous runs.
Mounting: Adjustable steel brackets, available in different lengths.
Dimensions/Weight: 14.4" (1.21 lbs) – 24.8" (1.76 lbs) – 36.6" (2.43 lbs) – 48.4" (3.09 lbs) – 60.2" (3.75 lbs)

Driver: Integral, 120/277VAC Non-Dim. Remote mounted CV 24VDC.
Wattages CV: 6.4W (14.4") – 11W (24.8") – 16.5W (36.6") – 22W (48.4") – 27.5W (60.2")
Wattages IND: 7.2W (14.4") – 12.3W (24.8") – 18.5W (36.6") – 24.6W (48.4") – 30.8W (60.2")
Cable: Fixture comes with 9.8" of cable (Power cable required, ordered separately).
Safety features: Built-in TCS® (Moisture protection), Over tension and Electrical discharge protection systems.

IP rating: IP66. Fixture is protected against dust and direct exposure to powerful water jets.
IK rating: IK 10
ETL Certification: ETL, wet location

Optics: Fixed. Available in Elliptical Narrow Flood – Asymmetric Wall Washer – General Distribution. Anti-glare visors available as accessory.
Color temperatures: 2200K – 2700K – 3000K – 3500K – 4000K.
CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.
Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.

Delivered Lumens*	14.4"	24.8"	36.6"	48.4"	60.2"
GE	297	509	763	1017	1271
ELNFL	946	1621	2431	3241	4051
WW	958	1642	2463	3283	4104

*Values shown for 3000K

CV - REMOTE DRIVER

Ordering Information											
XE	W	OB									
Product	**Mounting/ Frame**	**Type**	**Length**	**Wattage/Operation**	**Color Temp**	**Optic**	**+**	**Driver (Required)[1]**	**Cables[1]**	**Fixing Brackets[1]**	**Anti-glaring[1]**
XE = Xenia	W = Wall	OB = Open Beam	14 = 14.4"	6 CV = 6.4W / Remote Constant Voltage 24V DC Driver	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	ELNFL = Elliptical Narrow Flood (27°x 91°) WW = Asymmetric Wall Washer (87°) GE = General Distribution		OT96-D010 DI96-24V-JBX-DPH-D010 LUT96-L3D0 EL96-D010	E99216 E89190 E98437 E98149 E89188	98949 89045 89046 89047 C-F400006 C-F400008	98782 (14) 98783 (25) 98784 (37) 98785 (48) 99778 (60)
			25 = 24.8"	11 CV = 11W / Remote Constant Voltage 24V DC Driver							
			37 = 36.6"	17 CV = 16.5W / Remote Constant Voltage 24V DC Driver							
			48 = 48.4"	22 CV = 22W / Remote Constant Voltage 24V DC Driver							
			60 = 60.2"	28 CV = 27.5W / Remote Constant Voltage 24V DC Driver							

[1] See page 3

IND - INTEGRAL DRIVER


Ordering Information										
XE	W	OB								
Product	**Mounting/ Frame**	**Type**	**Length**	**Wattage/Operation**	**Color Temp**	**Optic**	**+**	**Cables[1]**	**Fixing Brackets[1]**	**Anti-glaring[1]**
XE = Xenia	W = Wall	OB = Open Beam	14 = 14.4"	7 IND = 7.2W / Integral (120/277VAC Non Dim)	22 = 2200K 27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	ELNFL = Elliptical Narrow Flood (27°x 91°) WW = Asymmetric Wall Washer (87°) GE = General Distribution		E83043 E83044 E83045 E83046 E83047	98949 89045 89046 89047 C-F400006 C-F400008	98782 (14) 98783 (25) 98784 (37) 98785 (48) 99778 (60)
			25 = 24.8"	12 IND = 12.3W / Integral (120/277VAC Non Dim)						
			37 = 36.6"	19 IND = 18.5W / Integral (120/277VAC Non Dim)						
			48 = 48.4"	25 IND = 24.6W / Integral (120/277VAC Non Dim)						
			60 = 60.2"	31 IND = 30.8W / Integral (120/277VAC Non Dim)						

[1] See page 3


Xenia Wall

inter•lux


14.4" 6.4W CV / 7.2W IND




24.8" 11W CV / 12.3W IND




36.6" 16.5W CV / 18.5W IND



48.4" 22W CV / 24.6W IND



60.2" 27.5W CV / 30.8W IND



DRIVER OPTIONS (pick one if ordering CV)

Power supply options (remote only)

OT96-D010	DI96-24V-JBX-DPH-D010	LUT96-L3D0	EL96-D010
eldoLED, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	0.1% Forward Phase or 0-10V, 96W, 24VDC 120-277AC, wet location	Lutron 24VDC 96W 0.1% EcoSystem dimming 120/277V	eldoLED 24VDC 96W 0.1% 0-10V dimming 120/277V

Cables

E83043	E83044	E83045	E83046	E83047
59" line volt. power feed cable F 3 pin M12	196" line volt. power feed cable F 3 pin M12	39" line volt. power extension cable M+F 3 pin M12	196" line volt. power extension cable M+F 3 pin M12	393" line volt. power extension cable M+F 3 pin M12
E99216[2]	**E89190**[2]	**E98437**[3]	**E98149**[3]	**E89188**[3]
59.1" DC(+) power cable F 4 pin M12	196.9" DC(+) power cable F 4 pin M12	39" extension power cable M+F 4 pin M12	196.9" extension power cable M+F 4 pin M12	393.7" extension power cable M+F 4 pin M12

[2] One Female DC(+) and Male DC(-) required per driver
[3] Required between fixtures powered from the same driver

Accessories

Steel fixing brackets (Pair)

1.8-2.6"	98949
3.5"	89045
5.9"	89046
11.8"	89047




Anti-glaring accessory


14.4"	98782
24.8"	98783
36.6"	98784
48.4"	98785
60.2"	99778



Brackets for surface mounting



C-F400006 (Pair)



C-F400008 (Pair)